

METAL PLATE  
EMBOSSER



C330

## C330

Compact Metal Plate Embosser

**Matica C330 has been specifically designed to provide low to medium volume of metal plates. It is the ideal solution for industrial applications that require lower processing speed or as a back-up unit for larger systems. The C330 offers the advantages of an automatic plate together with robustness at a very competitive price.**

The design of the C330 is modern and ergonomic, and at the same time robust and user-friendly. The cover, made in a combination of aluminum and self-extinguishable polycarbonate, allows the system to withstand harsh industrial environments thus ensuring its perfect conditioning over time. The C330 features a silent embossing mechanism, therefore it is suitable to be placed in any industrial or office environment, considering also the compact shape and small size.

The C330 is equipped with an automatic loading hopper of 200 plates (0,5mm thickness) and finished plates are ejected through a side slot into a removable box. The universal plate feeder can fit measures from 50x20 to 90x60mm. Matica C330 can be configured for either embossing or indenting applications, using a wide choice of type styles, and

operator can manually adjust the machine for varying plate dimensions based on application requirements.

Matica C330 incorporates the Xon Xoff protocol and is compatible with Windows Generic printer driver. Production can be easily managed by any Windows based application. Other protocols are available for legacy machine replacement.

Data entry can either be performed through a keyboard using the integrated sophisticated off-line editor.

- Compact and modern design
- Ideal for low to medium volumes
- Silent embossing mechanism
- Variable plate and font size
- Manageable on-line and off-line




# C330

## Compact Metal Plate Embosser

### TECHNICAL SPECIFICATIONS

<b>Productivity</b>	Up to 100 plates/hours (45 ch/plate) Recommended operating time: 4 hours/day
<b>Plate Handling</b>	Universal plate feeder Input hopper capacity: 200 plates (0.5 mm thickness) Side Eject Universal Clamp Holder
<b>Plate Personalization</b>	Minimum plate dimensions (L x W): 50 mm x 20 mm Maximum plate dimensions (L x W): 90 mm x 60 mm Non - embossing area: 5mm from clamp side
<b>Embossing Drum</b>	Embossing drum: 60 characters
<b>Available Characters</b>	Simplex 2 (350) - 3 mm embosser Simplex 3 (489) - 4 mm embosser USA Block (490) - 4 mm Other fonts available on request All fonts are available in Standard or Reverse version
<b>Interface</b>	USB interface (USBtoCom driver) Protocol: Xon/Xoff, CHIP, L2, ## Storable format layouts: 4 of 15 fields x 32 characters LAN optional PS2 Keyboard Interface (keyboard not included)
<b>Other Features</b>	LCD display (40 x 2) + 1 Clear button
<b>Warranty</b>	1 year or 150.000 plates
<b>Dimension (L x W x H)</b>	61 x 43 x 25 cm
<b>Weight</b>	Weight: 25,5 Kg
<b>Electrical Requirements</b>	Power Supply: 100 to 240 VAC; 50/60 Hz, 200 Watt
<b>Operating environment</b>	Temperature: 5 ÷ 40 °C Humidity: 30% ÷ 90% non condensing



- Military & Aerospace
- Steel & Metal Treatment Plants
- Automotive
- Electric Motors & Pump
- Shipyards

Authorized Reseller / System Integrator